

COSHEEN

SOFT VELVET FINISH INTERIOR PAINT



DESCRIPTION

CoSheen is a premium paint that combines exceptional hide with superior durability, washability and block resistance. CoSheen smoothness makes it ideal for use in high-end commercial projects areas such as living rooms, dining rooms, bedrooms, hallways and other surfaces requiring an eggshell finish.

RECOMMENDED FOR

Interior applications on plaster, embossed wall coverings, gypsum board, wood and other properly primed and prepared surfaces.

KEY FEATURES

- No lead
- Very low water absorption
- Reduced dirt pick-up
- Good durability
- Good opacity
- Odorless

PHYSICAL PROPERTIES

Solvent Type	Waterborne	
Finish Type	Gloss Level 3, Eggshell-like finish.	10 to 25 units at 60 degrees and 10 to 35 units at 85 degrees
Gloss Values	(20/60/85) = 1, 11, 21 - Eggshell 21	Based on ASTM D523
Spreading Rate	Approximately 8-9 m ² /kg/coat 2-3 coats recommended depending on surface porosity and application techniques N bases might require additional coat depending on color	
Average Dry Time	Touch-dry in 1/2-1 hour	Based on ASTM D 1640
Recoat	After 2-4 hours.	
Flash Point	Not Applicable	
Dry Film Thickness	40 to 45 microns depending on application	
Thinner	Add up to 15% of clean water for first coat and up to 20% of clean water for the following coats	
Contrast Ratio (Dry Opacity)	96.5% ±0.3 at 100-micron WFT 98.6% ±0.3 at 200-micron WFT	ASTM D2805
Adhesion	1 N/mm ²	Based on ASTM D4541.
Scrub Resistance	Higher than 10 000 cycles	Based on ASTM D2486
Density	PW = 1.29 g/cm ³ , W0 = 1.25 g/cm ³ , W1 = 1.14 g/cm ³ , N = 1.07 g/cm ³	
Solids	PW=50.07%, W0=47.74%, W1=41.11%, N= 35.67%	
Viscosity	10,000 - 15,000 cP	Measured with Spindle 4 at Speed 5
VOC	Maximum of 30 g/L Testing Methods Used <ul style="list-style-type: none"> • ASTM D6886 • EPA Method 24(ASTM D2369) • ASTM D3960 • UL 2821 • ISO 11890-2 	<ul style="list-style-type: none"> • Compliant with GS-11 Standards, 1993 • Compliant with UL 2818 - 2013 Gold Standard • Compliant with LEED 2009 • Compliant with LEED V4 • Compliant with EU Directive 2004/42/EC • Compliant with SCAQMD Rule 1113, 2004 • Compliant with California Department of Public Health (CDPH) Standard Method V1.1-2010
Bases	PW, W0, W1, N	
Colors	Available in Pure White Tintable in all colors	

COLORTEK®
Wall Floor and Fashion

info@colortek.eu
www.colortek.eu



COSHEEN

SOFT VELVET FINISH INTERIOR PAINT



medical attention immediately.

CLEANING

Remove as much leftover product as possible from the application equipment before cleaning. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Do not empty product into drains or watercourses.

TECHNICAL ASSISTANCE

Available through your local COLORTEK® Design Center or through your COLORTEK PAINTS® authorized distributor. For the location of the retailer nearest you, email us at info@colortek.eu or check our website www.colortek.eu.

DISCLAIMER

Product batches are subject to stringent quality control checks in conformity with ISO 9001:2015, Certificate LB18/234269. The information submitted in this manual is correct to the best of our knowledge & experience. No liability whatsoever can be accepted based on the information supplied herein.

COLORTEK®
Wall Floor and Fashion

info@colortek.eu
www.colortek.eu

